

Hooter Cum Strobe

XF-HS1R



SALIENT FEATURES

- ABS plastic body
- 3 selectable tones
- High sound output/ Light source

Specification

Model	XF-HS1R
Voltage	20-30Volt DC
Alarm Current	95mA
Dimension (mm)	185 x 130 x 70(mm)
Sound Output	≥100db/1m
Light	≥1.2WS with 2 seconds cycle
Color	Red
Material of Cons.	FR Polymer

Response Indicator

XF-RI1W



SALIENT FEATURES

- Dual LED
- Low Current Consumption

Specification

Model	XF-RI1W
Voltage	6-26 Volt DC
Alarm Current	16m A
Weight	32gm
Dimension	95 x 65 x 30
Color	White
Material of Cons.	FR Polymer

Manual Call Point

XF-CP1R



SALIENT FEATURES

- Available for Flush or Surface mounting.
- Suitable for majority of conventional Fire Alarm system.
- Front Protection glass cover.
- Unbreakable glass ABS plastic body

Specification

Model	XF-CP1R
Voltage	18-26 Volt DC
Alarm Current	30m A
Weight	140gm
Dimension (mm)	85 x 85 x 50
Color	Red
Material of Cons.	FR Polymer

Hooter/Sounder

XF-HT1R



SALIENT FEATURES

- 24/12 Volt DC operation.
- High sound output with low current consumption.

Specification

Model	XF-HT1R
Voltage	20-26 Volt DC
Alarm Current	180m A
Weight	370gm
Dimension	115 x 115 x 75
Color	Red
Material of Cons.	FR Polymer